

Part No. 6608xxWV051
DWG NO. C6608WV

RECOMMENDED PCB LAYOUT
(PCB THK=1.0~1.6)

Dimensional & Ordering Information:

Part No.	Circuits	Dim A	Dim B	Dim C
660802WV051	2	4.14	9.72	5.66
660803WV051	3	8.28	13.86	5.66
660804WV051	4	12.42	18.00	5.66
6608A4WV051	4	4.14	9.72	9.8
660806WV051	6	8.28	13.86	9.8
660808WV051	8	12.42	18.00	9.8
660808WV051	9	8.28	13.86	13.94
660810WV051	10	16.56	22.14	9.8
6608A12WV051	12	20.7	26.28	9.8
660812WV051	12	12.42	18.00	13.94
660814WV051	14	24.84	30.42	9.8
660815WV051	15	16.56	22.14	13.94
660816WV051	16	28.98	34.56	9.8
660818WV051	18	33.12	38.70	9.8
660820WV051	20	37.26	42.84	9.8
660822WV051	22	41.4	46.98	9.8
660824WV051	24	45.54	51.12	9.8

NOTE:

- Housing Material:Nylon 66 UL94V2 or V0
- Color: Natural
- Withstand voltage: 1500V AC/minute.
- Current rating: 5A AC/DC.
- Voltage rating: 600V AC/DC

EXCON
EXCON TECHNOLOGY COMPANY

REV. REVISIONI DIS DATE
SCALE REV. PAGE: UNIT mm DWG NO: PART.NO
NONE B 1 THIRD ANGLE PROJECTION C6608WV 6608xxWV051